

DURA-PUMP™

PRODUCT SPECIFICATIONS



Series	DP-4000
Check Valve	Internal; EPA 165.45 compliant
Vertical Suction Lift	Self-priming to 10ft
Pump Type	Self-priming, Positive Displacement Diaphragm pump
Chemically Resistant	Yes
Thermal Overload Protection	Yes
Run-Dry Capability	Yes
Internal Bypass	Yes
Run Time	30 Minute Duty Cycle
Operating Temp	-10°F to -130°F
Flow Rate	Max: 15GPM
Discharge Pressure	Max: 22psi
Motor Enclosure	Sealed
Suction Port	2" Male and 1" Female NPT thread
Discharge Port	1" Female NPT thread
Upper Housing	Glass-filled Polypropylene
Bottom Housing	Glass-filled Polypropylene
Diaphragm	Santoprene
Fluid	Non-flammable
Power Cord	12 Volt: 20ft; 110 Volt: 6.5ft
Wetted Material	Polypropylene; 304 Stainless Steel; Santoprene; EPDM or Viton® Seals
12 Volt DC Motor	185 Watts 18.5 Amps; 30 Amp In-Line Fuse Copperplated Alligator Clips
110 Volt DC Motor	185 Watts 2.0 Amps; 3 Amp In-Line Fuse 3 Prong Grounded Plug
Motor HP	12 Volt: 1/4 HP; 110 Volt: 1/4 HP

- / High-Flow with up to 15GPM flow rate
- / Self-priming diaphragm pump with internal by-pass
- / Motor thermally protected from overheating
- / 30 minute duty cycle
- / Suction ports has 2" Male NPT and 1" Female NPT
- / Pump is easily field serviceable
- / Features 2 Year Service Warranty Plan

DP-4012 12 volt

DP-4015 110 volt

(Available in EPDM or Viton®)

Must specify EPDM (**product # and E**) or Viton® (**product # and V**) when ordering.



DURA PRODUCTS
Technology with Lasting Value

www.DuraProducts.com
Arcadia, IN 46030 | 855-502-3872

©2015 Dura Products, Inc.